

IES10-SW8**Weidmüller Interfaces GmbH & Co. KG**

Postfach 3030

32760 Detmold

Tel. +49 5231 14-0

Fax. +49 5231 14-2083

info@weidmueller.com

www.weidmueller.com



IES10 series entry-level industrial Ethernet switches are unmanaged plug-and-play switches with tough metal housing and IP40 protection level. This series supports fast Ethernet and provides an economical and practical solution for your industrial Ethernet applications.

- Economical switch with high performance
- Compact housing
- 5 or 8 RJ45 fast Ethernet ports
- Single power input: 24/48VDC(18~72VDC), 24/48VAC(18~50VAC)
- Operating temperature range: 0°C ...+60°C

General ordering data

Version	8x RJ45 10/100BaseT(X), Din-Rail(wall) mounting products, Unmanaged IE Switch
Order No.	7760048002
Type	IES10-SW8
GTIN (EAN)	6944169638220
Qty.	1 Stück
Delivery status	This article will no longer be available in the future.
Local product	Only available in certain countries

IES10-SW8

Weidmüller Interfaces GmbH & Co. KG

Postfach 3030

32760 Detmold

Tel. +49 5231 14-0

Fax. +49 5231 14-2083

info@weidmueller.com

www.weidmueller.com

Technische Daten

General ordering data

Local product

Only available in certain countries

Dimensions and weights

Height	135 mm	Height (inches)	5.315 inch
Width	53.6 mm	Width (inches)	2.11 inch
Length	106.5 mm	Length (inches)	4.193 inch
Net weight	760 g		

Temperatures

Storage temperature	-40 °C...+85 °C	Operating temperature	0 °C...+60 °C
Humidity	5 to 95 % (non-condensing)		

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1	SCIP	9229992a-00b9-4096-8962-200a7f3
------------	----------------	------	---------------------------------

Approvals

EMI		EMS	IEC 61000-4-2 Electrostatic discharge: ±8kV contact discharge, ±15kV air discharge; IEC 61000-4-3 Radiated RFI: 10V/m (80MHz~1GHz); IEC 61000-4-4 Fast transient/burst: DC/ AC power port: ±4kV; data port: ±2kV; IEC 61000-4-5 Surge: DC/AC power port: ±2kV (line- line), ±4kV (line-earth); IEC 61000-4-6 conducted RFI: DC/AC power port: 10V (150 kHz~80MHz)
	FCC CFR47 Part 15, CISPR22 (EN 55022) Class A		
Free fall	IEC 60068-2-32	Railway	EN 50155, EN 50121-4
EMC standards	CE, FCC	Shock resistance IEC 60068-2-27	Available
Vibration resistance IEC 60068-2-6	Available	General Industry	IEC61000-6-2
Security	UL508	Hazardous environment	UL1604 Class 1 Div 2 (pending)

Cable

Twisted Pair	100 m (standard CAT5, CAT5e LAN cable)
--------------	---

Power Supply

Connection type	3 pole 5.08mm pitch terminal block	Input voltage	24V DC/AC (18~72 VDC / 18~50 VAC)
Overload protection	Yes	Power consumption	≤2.9 W
Redundant power supply	No	Reverse polarity protection	Yes

Erstellungs-Datum July 8, 2022 3:35:03 PM CEST

Katalogstand 01.07.2022 / Technische Änderungen vorbehalten

IES10-SW8

Weidmüller Interfaces GmbH & Co. KG

Postfach 3030

32760 Detmold

Tel. +49 5231 14-0

Fax. +49 5231 14-2083

info@weidmueller.com

Technische Daten

Technology

Diagnosis	LED (power supply and port)	Network structure	www.weidmueller.com star, line
-----------	-----------------------------	-------------------	--

Environmental conditions

Humidity	5 to 95 % (non-condensing)
----------	----------------------------

Guarantee

Time interval	5 years
---------------	---------

Interfaces

LED indicator	Power LED: PWR, Port LED: Link/ACT, Speed (RJ45 port)	Number of ports	8x RJ45 10/100BaseT(X)
---------------	---	-----------------	------------------------

Technical data

Housing main material	fanless, metal	Number of ports	8x RJ45 10/100BaseT(X)
Type of mounting	Rail, TS 35, Wall mounting		

Classifications

ETIM 6.0	EC000734	ETIM 7.0	EC000734
ETIM 8.0	EC000734	ECLASS 9.0	19-17-01-06
ECLASS 9.1	19-17-01-06	ECLASS 10.0	19-17-04-01
ECLASS 11.0	19-17-04-01	ECLASS 12.0	19-17-04-01

Approvals

Approvals



Downloads

Catalogues	Catalogues in PDF-format
------------	--